

TECHNICAL DATA


| | |
|--------------------------------|--|
| Assembly | with 3 screws M6, after preparing mounting holes in the column |
| Application | aluminium columns with spigot endings Ø60 i Ø76 mm |
| Colour | Blue, Green, Red, White |
| Ingress protection | IP 65 or IP 44 (after mounting on the column) |
| Material | PMMA (IP 44), HDPE (IP 65) |
| Input voltage frequency | 50/60Hz |




TABLE OF VARIANTS

| Symbol | LED power | Luminaire power consumption | Mounting diameter | Net weight |
|-------------------|-----------|-----------------------------|-------------------|------------|
| Small light spike | 6 W | 8.5 W | 76 mm | 0.6 kg |
| Small light spike | 6 W | 8.5 W | 76 mm | 0.6 kg |
| Small light spike | 6 W | 8.5 W | 76 mm | 0.6 kg |
| Small light spike | 6 W | 8.5 W | 76 mm | 0.6 kg |
| Small light spike | 1 W | 1.2 W | 76 mm | 0.75 kg |
| Small light spike | 1 W | 1.2 W | 76 mm | 0.75 kg |
| Small light spike | 1 W | 1.2 W | 76 mm | 0.75 kg |
| Small light spike | 1 W | 1.2 W | 76 mm | 0.75 kg |
| Small light spike | 1 W | 1.2 W | 60 mm | 0.55 kg |
| Small light spike | 1 W | 1.2 W | 60 mm | 0.55 kg |
| Small light spike | 1 W | 1.2 W | 60 mm | 0.55 kg |
| Small light spike | 1 W | 1.2 W | 60 mm | 0.55 kg |

IP44



IP44



IP65

