




TECHNICAL DATA

Assembly	with 3 screws M6, after preparing mounting holes in the column
Application	aluminium columns with spigot endings Ø60 i Ø76 mm
Ingress protection	IP 44 lub IP65 (po zamontowaniu na słupie)
Material	PMMA (IP 44), HDPE (IP 65)
Input voltage frequency	50 - 60Hz


TABLE OF VARIANTS

Code	Symbol	LED power	Luminaire power consumption	Colour		Mounting diameter	Net weight
40530	Small light spike fi 76-white IP 65	6 W	7 W	White	IP 65	76 mm	0,6 kg
40520	Small light spike fi 76-red IP 65	6 W	7 W	Red	IP 65	76 mm	0,6 kg
40510	Small light spike fi 76-green IP 65	6 W	7 W	Green	IP 65	76 mm	0,6 kg
40500	Small light spike fi 76-blue IP 65	6 W	7 W	Blue	IP 65	76 mm	0,6 kg
4053	Small light spike fi 76-white	1 W	1,2 W	White	IP 44	76 mm	0,75 kg
4052	Small light spike fi 76-red	1 W	1,2 W	Red	IP 44	76 mm	0,75 kg
4051	Small light spike fi 76-green	1 W	1,2 W	Green	IP 44	76 mm	0,75 kg
4050	Small light spike fi 76-blue	1 W	1,2 W	Blue	IP 44	76 mm	0,75 kg
4037	Small light spike fi 60-white	1 W	1,2 W	White	IP 44	60 mm	0,55 kg
4036	Small light spike fi 60-red	1 W	1,2 W	Red	IP 44	60 mm	0,55 kg
4035	Small light spike fi 60-green	1 W	1,2 W	Green	IP 44	60 mm	0,55 kg
4034	Small light spike fi 60-blue	1 W	1,2 W	Blue	IP 44	60 mm	0,55 kg

IP44



IP44



IP65

