



TECHNICAL DATA

Application	residential roads (internal), surrounding office buildings, parks, pedestrians, parkings
Colour	grey / inox
Ingress protection	IP 66 for the optical part and the driver
Optical system	PMMA optics, interchangeable LED module
Material	anodised aluminium alloy
Unit volume	1.1 m ³
Expected useful lifetime	L90B10 - 100 000 h
CRI	>70
Inrush current	18 A / 280 μs (STICK LED 24) 46 A / 250 μs (STICK LED 48; STICK II LED: 24, 90 24, 180 24; STICK III LED 90-90 24) 53 A / 300 μs (STICK II LED: 48, 90 48, 180 48; STICK III LED 90-90 48; STICK IV LED: 24, 90 24) 106 A / 300 μs (STICK IV LED: 48, 90 48)
Input voltage frequency	50/60Hz
Power factor	≥0.95
	12 - (STICK LED 24 W) 24 - (STICK LED 48 W), 2x12 - (STICK II LED 24 W), 2x24 - (STICK II LED 48 W), 3x12 - (24 W), 3x24 - (48 W), 4x12 - (24 W), 4x24 - (48 W),
Control system	LED lighting set has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1-10V).



TABLE OF VARIANTS

Code	Symbol	Height of the column [H]	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux ¹	Luminaire luminous flux ¹	Luminous efficacy ¹	Unit volume	Concrete footing / reinforcement basket type	Fasteners	Net weight	Inrush current
217030/1/... ²	STICK LED 24	5 m	24 W	28 W	700 mA	2700 K	4050 lm	3250 lm	116 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217030/3/... ²	STICK LED 24	5 m	24 W	28 W	700 mA	3500 K	4350 lm	3500 lm	125 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217030/4/... ²	STICK LED 24	5 m	24 W	28 W	700 mA	4000 K	4550 lm	3650 lm	130 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217030/6/... ²	STICK LED 24	5 m	24 W	28 W	700 mA	5000 K	4550 lm	3650 lm	130 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217033/1/... ²	STICK LED 48	5 m	48 W	55 W	700 mA	2700 K	8150 lm	5700 lm	104 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217033/3/... ²	STICK LED 48	5 m	48 W	55 W	700 mA	3500 K	8650 lm	7000 lm	127 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217033/4/... ²	STICK LED 48	5 m	48 W	55 W	700 mA	4000 K	9150 lm	7400 lm	135 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217033/6/... ²	STICK LED 48	5 m	48 W	55 W	700 mA	5000 K	9150 lm	7400 lm	135 lm/W	1.1 m ³	B-60 / Z-60	4008	61 kg	-
217130/1/... ²	STICK II LED 24	5 m	24 W x 2	28 W x 2	700 mA	2700 K	4050 lm x 2	3249 lm x 2	116 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217130/3/... ²	STICK II LED 24	5 m	24 W x 2	28 W x 2	700 mA	3500 K	4350 lm x 2	3500 lm x 2	125 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217130/4/... ²	STICK II LED 24	5 m	24 W x 2	28 W x 2	700 mA	4000 K	4550 lm x 2	3650 lm x 2	130 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217130/6/... ²	STICK II LED 24	5 m	24 W x 2	28 W x 2	700 mA	5000 K	4550 lm x 2	3650 lm x 2	130 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217133/1/... ²	STICK II LED 48	5 m	48 W x 2	55 W x 2	700 mA	2700 K	8150 lm x 2	6600 lm x 2	120 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217133/3/... ²	STICK II LED 48	5 m	48 W x 2	55 W x 2	700 mA	3500 K	8650 lm x 2	7000 lm x 2	127 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217133/4/... ²	STICK II LED 48	5 m	48 W x 2	55 W x 2	700 mA	4000 K	9150 lm x 2	7400 lm x 2	135 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217133/6/... ²	STICK II LED 48	5 m	48 W x 2	55 W x 2	700 mA	5000 K	9150 lm x 2	7400 lm x 2	135 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217230/1/... ²	STICK II LED 90 24	5 m	24 W x 2	28 W x 2	700 mA	2700 K	4050 lm x 2	3250 lm x 2	116 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217230/3/... ²	STICK II LED 90 24	5 m	24 W x 2	28 W x 2	700 mA	3500 K	4350 lm x 2	3500 lm x 2	125 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217230/4/... ²	STICK II LED 90 24	5 m	24 W x 2	28 W x 2	700 mA	4000 K	4550 lm x 2	3650 lm x 2	130 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-

217230/6/... ²	STICK II LED 90 24	5 m	24 W x2	28 W x 2	700 mA	5000 K	4550 lm x2	3650 lm x 2	130 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217233/1/... ²	STICK II LED 90 48	5 m	48 W x2	55 W x 2	700 mA	2700 K	8150 lm x2	6600 lm x 2	120 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217233/3/... ²	STICK II LED 90 48	5 m	48 W x2	55 W x 2	700 mA	3500 K	8650 lm x2	7000 lm x 2	127 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217233/4/... ²	STICK II LED 90 48	5 m	48 W x2	55 W x 2	700 mA	4000 K	9150 lm x2	7400 lm x 2	135 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217233/6/... ²	STICK II LED 90 48	5 m	48 W x2	55 W x 2	700 mA	5000 K	9150 lm x2	7400 lm x 2	135 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217330/1/... ²	STICK II LED 180 24	5 m	24 W x2	28 W x 2	700 mA	2700 K	4050 lm x2	3250 lm x 2	116 lm/W	1.1 m ³	B-60 / Z-60	4008	62 kg	-
217330/3/... ²	STICK II LED 180 24	5 m	24 W x2	28 W x 2	700 mA	3500 K	4350 lm x2	3500 lm x 2	116 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217330/4/... ²	STICK II LED 180 24	5 m	24 W x2	28 W x 2	700 mA	4000 K	4550 lm x2	3650 lm x 2	130 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217330/6/... ²	STICK II LED 180 24	5 m	24 W x2	28 W x 2	700 mA	5000 K	4550 lm x2	3650 lm x 2	130 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217333/1/... ²	STICK II LED 180 48	5 m	48 W x2	55 W x 2	700 mA	2700 K	8150 lm x2	6600 lm x 2	120 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217333/3/... ²	STICK II LED 180 48	5 m	48 W x2	55 W x 2	700 mA	3500 K	8650 lm x2	7000 lm x 2	127 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217333/4/... ²	STICK II LED 180 48	5 m	48 W x2	55 W x 2	700 mA	4000 K	9150 lm x2	7400 lm x 2	135 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217333/6/... ²	STICK II LED 180 48	5 m	48 W x2	55 W x 2	700 mA	5000 K	9150 lm x2	7400 lm x 2	135 lm/W	1.1 m ³	B-60 / Z-60	4008	67 kg	-
217430/1/... ²	STICK III LED 90-90 24	5 m	24 W x3	28 W x 3	700 mA	2700 K	4050 lm x3	3250 lm x 3	116 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217430/3/... ²	STICK III LED 90-90 24	5 m	24 W x3	28 W x 3	700 mA	3500 K	4350 lm x3	3500 lm x 3	125 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217430/4/... ²	STICK III LED 90-90 24	5 m	24 W x3	28 W x 3	700 mA	4000 K	4550 lm x3	3650 lm x 3	130 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217430/6/... ²	STICK III LED 90-90 24	5 m	24 W x3	28 W x 3	700 mA	5000 K	4550 lm x3	3650 lm x 3	130 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217433/1/... ²	STICK III LED 90-90 48	5 m	48 W x3	55 W x 3	700 mA	2700 K	8150 lm x3	6600 lm x 3	120 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217433/3/... ²	STICK III LED 90-90 48	5 m	48 W x3	55 W x 3	700 mA	3500 K	8650 lm x3	7000 lm x 3	127 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217433/4/... ²	STICK III LED 90-90 48	5 m	48 W x3	55 W x 3	700 mA	4000 K	9150 lm x3	7400 lm x 3	135 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217433/6/... ²	STICK III LED 90-90 48	5 m	48 W x3	55 W x 3	700 mA	5000 K	9150 lm x3	7400 lm x 3	135 lm/W	1.1 m ³	B-60 / Z-60	4008	73 kg	-
217630/1/... ²	STICK IV LED 24	5 m	24	28 W x 4	700 mA	2700 K	4050 lm x4	3250 lm x 4	116 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217630/3/... ²	STICK IV LED 24	5 m	24	28 W x 4	700 mA	3500 K	4350 lm x4	3500 lm x 4	125 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217630/4/... ²	STICK IV LED 24	5 m	24	28 W x 4	700 mA	4000 K	4550 lm x4	3650 lm x 4	130 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217630/6/... ²	STICK IV LED 24	5 m	24	28 W x 4	700 mA	5000 K	4550 lm x4	3650 lm x 4	130 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217633/1/... ²	STICK IV LED 48	5 m	48	55 W x 4	700 mA	2700 K	8150 lm x4	6600 lm x 4	120 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217633/3/... ²	STICK IV LED 48	5 m	48	55 W x 4	700 mA	3500 K	8650 lm x4	7000 lm x 4	127 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217633/4/... ²	STICK IV LED 48	5 m	48	55 W x 4	700 mA	4000 K	9150 lm x4	7400 lm x 4	135 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217633/6/... ²	STICK IV LED 48	5 m	48	55 W x 4	700 mA	5000 K	9150 lm x4	7400 lm x 4	135 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217730/1/... ²	STICK IV LED 90 24	5 m	24	28 W x 4	700 mA	2700 K	4050 lm x4	3250 lm x 4	116 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217730/3/... ²	STICK IV LED 90 24	5 m	24	28 W x 4	700 mA	3500 K	4350 lm x4	3500 lm x 4	125 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217730/4/... ²	STICK IV LED 90 24	5 m	24	28 W x 4	700 mA	4000 K	4550 lm x4	3650 lm x 4	130 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217730/6/... ²	STICK IV LED 90 24	5 m	24	28 W x 4	700 mA	5000 K	4550 lm x4	3650 lm x 4	130 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217733/1/... ²	STICK IV LED 90 48	5 m	48	55 W x 4	700 mA	2700 K	8150 lm x4	6600 lm x 4	120 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217733/3/... ²	STICK IV LED 90 48	5 m	48	55 W x 4	700 mA	3500 K	8650 lm x4	7000 lm x 4	127 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-

217733/4/... ²	STICK IV LED 90 48	5 m	48	55 W x 4	700 mA	4000 K	9150 lm x 4	7400 lm x 4	135 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-
217733/6/... ²	STICK IV LED 90 48	5 m	48	55 W x 4	700 mA	5000 K	9150 lm x 4	7400 lm x 4	135 lm/W	1.1 m ³	B-60 / Z-60	4008	79 kg	-

1) tolerance +/- 5% due to LEDs accuracy

2) symbol of chosen optical system eg. 217030/3/T2 is a bracket STICK LED 24 3500K with T2 optical system


DIRECTIVES AND STANDARDS

DIRECTIVES: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC (Official Journal of the UE L 285/10 31.10.2009)


STANDARDS: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019, PN-EN 61000-3-3: 2014

Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

TECHNICAL DRAWING



PHOTOMETRIC CURVES



POWER SYSTEM FUNCTIONS

Luminaire in standard has following functions of intelligent power supply:

- Connection to outside control system by DALI interface (operation of analog signal 1-10V as an option),
- Possibility of programming multistage dimming of luminaire, up to 5 intervals in the range of from 10 to 100% of nominal power,
- LED module equipped with thermal protection implemented via an NTC thermistor,
- Regulation of power / luminous flux – the option of setting another value than the catalogue in the range of 30-100% of nominal one,

ACCEPTABLE QUANTITY OF LUMINAIRES ON ONE CIRCUIT

Overcurrent switches MCB type B or C

Lighting set	Type	2A	4A	6A	10A	16A	20A	25A
STICK LED 24	B	3	6	10	16	26	32	40
	C	3	10	16	27	44	54	67
STICK II LED 24 STICK LED 48 STICK III LED 24	B	1	2	4	6	11	13	17
	C	1	4	6	11	18	22	28
STICK II LED 48 STICK III LED 48 STICK IV LED 24	B	1	2	3	5	8	10	12
	C	1	3	5	8	13	16	20
STICK IV LED 48	B	0	1	1	2	4	5	6
	C	0	1	2	4	6	8	10

Fuse – type gG and GL

Lighting set	2A	4A	6A	10A	16A	20A	25A
STICK LED 24	1	10	19	25	50	68	97
STICK II LED 24 STICK LED 48 STICK III LED 24	0	4	8	11	21	29	42
STICK II LED 48 STICK IV LED 24	0	3	6	8	17	23	33
STICK III LED 48	0	3	6	8	17	22	27
STICK IV LED 48	0	1	3	4	8	11	16

ACCEPTABLE HEIGHT

STICK I LED	Acceptable height of the LED lighting set			
Field category	I zone Vref. = 22 m/s	I & III zone, up to 450m a.s.l. Vref. = 24 m/s	II zone Vref. = 26 m/s	III zone up to 755m a.s.l. Vref. = 28 m/s
I	6	5,5	5	4,5
II	6	5,5	5,5	5
III	6	6	5,5	5,5
IV	6	6	6	6

STICK II LED	Acceptable height of the LED lighting set			
Field category	I zone Vref. = 22 m/s	I & III zone, up to 450m a.s.l. Vref. = 24 m/s	II zone Vref. = 26 m/s	III zone up to 755m a.s.l. Vref. = 28 m/s
I	5,5	5	4,5	4
II	6	5,5	5	4,5
III	6	6	5,5	5
IV	6	6	6	5,5

STICK III/IV LED	Acceptable height of the LED lighting set			
Field category	I zone Vref. = 22 m/s	I & III zone, up to 450m a.s.l. Vref. = 24 m/s	II zone Vref. = 26 m/s	III zone up to 755m a.s.l. Vref. = 28 m/s
I	5,5	5	4,5	4
II	5,5	5	4,5	4,5
III	6	5,5	5	5
IV	6	6	5,5	5,5