


176 mm at the base plate



Anodising	10 colours
Luminaire mounting	directly on the extension arm, luminaires with ø60 mm mounting with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet
Packing	sleeve material
Performance under vehicle impact (passive safety)	50-NE-C-S-SE-MD-0, 70-NE-C-S-SE-MD-0, 100-NE-C-S-SE-MD-0
Diameter at the base plate	176 mm
Finish	brushed anodised aluminium - anode coating thickness is 20µm as standard (coating thickness of 25µm is also possible), option of elastomer protection in column's colour up to a height of 350 mm (other height on customer's request) - the thickness of the protective coating ranges from 0.8 mm to 1.2 mm
Ingress protection	IP54 for wire chamber



Code	Symbol	Height of the column [H]	Unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners	Net weight
42451/C...	SAL-11 WŁ 1/1,5/4,7/5	11 m	0.82 m³	B-71 / Z-71	311171 / 311271	4012	60.7 kg

SAL-11 WL 1/1,5/4,7/5		Acceptable windage of single luminaire[m²] for Cx=1			
code 42451	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s	
Permissible weight of a single luminaire [kg]	zone I, terrain category III	zone I & III, terrain category III up to 450m a.s.l	zone II, terrain category III	zone III, terrain category III up to 755m a.s.l.	
15	0.28	0.19	0.12	0.08	

C-0 Natural

C-32 Champagne

C-33 Olive

C-34 Brown

C-35 Black

C-45 Inox

CI-63 Grey

CI-65 Graphite

CI-75 Green

CI-78 Anthracite