

ROSA



Diffuser	frosted (PMMA)
Power	70 W
Application	parks, pedestrians, bicycle routes
Assembly	pole top mounted or on extension arms with ø 60 x 50 mm ending
Colour	painted in black colour
Ingress protection	IP 65
Material	-
Input voltage frequency	50 Hz
Supply voltage	230V AC
Electrical gear cover	mounted on gear frame, magnetic ballast with thermal protection, metal halide lamps MH 70W (EL) optionally available with electronic ballast
Mounting method	only upwards
Light source type	sodium E-27

Code	Symbol	Diffuser	LED power	Luminaire power consumption	Unit volume	Effective projected area	Light source type	Exemplary lamp types	Net weight
2134002	ELBA S-70W, frosted diffuser PMMA	frosted (PMMA)	-	92 W	0.06 m³	0.115 m²	sodium E-27	Philips: SON 70W-E, CDO-ET (-TT) 70W Osram: NAV-E 70W	6.3 kg

DIRECTIVES: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC (Official Journal of the UE L 285/10 31.10.2009)

Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

Technical drawings of the LUMINAR LUMINAR 600x530mm ceiling light fixture. The left drawing shows the front view with a single light bulb. The right drawing shows the rear view with a grid of ventilation slots. Dimensions include a width of 600mm, a total height of 530mm, a mounting height of 420mm, a base diameter of Ø30, and a base width of Ø60 x 50.