


TECHNICAL DATA

Anodising	10 colours
Packing	bubble wrap
Dimension of the base plate (side [A]/ bolt spacing [B]/ thickness [C])	-
Assembly	on concrete footing or rooted (marked "dz" in the name)
Application	parks, pedestrians
Finish	grinded, anodised aluminium - anode coating thickness is 20µm as standard (coating thickness of 25µm is also possible), option of elastomer protection in the colour of the column up to the height of 50 mm (other height on customer's request) - the thickness of the protective coating ranges from 0.8 mm to 1.2 mm
Ingress protection	IP 65
Material	cylindrical aluminium tube, diffuser frosted PMMA tube
Input voltage frequency	50 Hz
Supply voltage	230V AC
Electrical gear cover	mounted on gear frame, magnetic ballast with thermal protection, metal halide lamps MH 70W (EL) optionally available with electronic ballast
Light source type	S-70W
Types of bollards	on concrete footing and rooted (marked "dz" in the name) with round and flat cap (marked .../P in the product code)
	-



Code	Symbol	Height of the column [H]	Unit volume	Concrete footing / reinforcement basket type	Light source type	Net weight
450068/C...	SAMR 900 dz S-70W	945 mm	0.036 m³	-	S-70W	6.75 kg

: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC (Official Journal of the UE L 285/10 31.10.2009)

: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019, PN-EN 61000-3-3: 2014

Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

TECHNICAL DRAWING

