


## TECHNICAL DATA

<b>Anodising</b>	10 colours
<b>Packing</b>	bubble wrap
<b>Application</b>	parks, pedestrians
<b>Finish</b>	grinded, anodised aluminium - anode coating thickness is 20µm as standard (coating thickness of 25µm is also possible), option of elastomer protection in the colour of the column up to the height of 50 mm (other height on customer's request) - the thickness of the protective coating ranges from 0.8 mm to 1.2 mm
<b>Ingress protection</b>	IP 65
<b>Material</b>	aluminium alloy tube, transparent cylindrical PMMA diffuser
<b>Input voltage frequency</b>	50 Hz
<b>Supply voltage</b>	230V AC
<b>Electrical gear cover</b>	mounted on gear frame, magnetic ballast with thermal protection, metal halide lamps MH 70W (EL) optionally available with electronic ballast
<b>Light source type</b>	compact fluorescent lamp E-27
<b>Types of bollards</b>	on concrete footing and rooted (marked "dz" in the name) with round and flat cap (marked .../P in the product code)



Code	Symbol	Height of the column [H]	Unit volume	Concrete footing / reinforcement basket type	Light source type	Net weight
45056/C...	SAP 1200 W E/Z	1 245 mm	0.031 m³	B-0A / Z-0A	compact fluorescent lamp E-27	5.35 kg

: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC(Official Journal of the UE L 285/10 31.10.2009)  
 : PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019, PN-EN 61000-3-3: 2014

Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

## TECHNICAL DRAWING

