



TECHNICAL DATA

Assembly	with 3 screws M6, after preparing mounting holes in the column
Application	aluminium columns with spigot endings $\varnothing 60$ i $\varnothing 76$ mm
Colour	Blue, Green, Red, White
Ingress protection	IP 65 or IP 44 (after mounting on the column)
Material	PMMA (IP 44), HDPE (IP 65)
Input voltage frequency	50/60Hz



TABLE OF VARIANTS

Symbol	LED power	Luminaire power consumption	Mounting diameter	Net weight
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg

