



## TECHNICAL DATA

<b>Assembly</b>	with 3 screws M6, after preparing mounting holes in the column
<b>Application</b>	aluminium columns with spigot endings $\varnothing 60$ i $\varnothing 76$ mm
<b>Colour</b>	Blue, Green, Red, White
<b>Ingress protection</b>	IP 65 or IP 44 (after mounting on the column)
<b>Material</b>	PMMA (IP 44), HDPE (IP 65)
<b>Input voltage frequency</b>	50/60Hz



## TABLE OF VARIANTS

Symbol	LED power	Luminaire power consumption	Mounting diameter	Net weight
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	6 W	7 W	76 mm	0.6 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	76 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg
Light ball	1 W	1.2 W	60 mm	0.4 kg

