



TECHNICAL DATA

Application	parks, pedestrians
Assembly	on columns, extension arms, aluminium and steel wall brackets with spigot ending Ø60 mm, 70 mm deep and on poles type S and SP with special adaption for this luminaire
Colour	black
Ingress protection	IP 44
Material	polyamide with fibre glass
Input voltage frequency	50/60Hz
Supply voltage	230V AC
Mounting method	only upwards
Type of luminaires	OZ 400 - lamp's diffuser collar diameter ø180 mm

TABLE OF VARIANTS

Code	Symbol	Power	Unit volume	Effective projected area	Colour	Light source type	Lamp diffuser neck	Type of diffuser	Net weight
211415	OZ 400	23 W	0.01 m³	0.13 m²	• black	LED E-27	180 mm	Sphere 400	0.35 kg

: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC(Official Journal of the UE L 285/10 31.10.2009)
: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019 , PN-EN 61000-3-3: 2014

Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

TECHNICAL DRAWING

