



## TECHNICAL DATA

<b>Assembly</b>	on columns, extension arms, aluminium and steel wall brackets with spigot ending $\varnothing 60$ mm, 70 mm deep and on poles type S and SP with special adaption for this luminaire
<b>Application</b>	parks, pedestrians
<b>Colour</b>	black
<b>Ingress protection</b>	IP 44
<b>Material</b>	polyamide with fibre glass
<b>Input voltage frequency</b>	50/60Hz
<b>Supply voltage</b>	230V AC
<b>Mounting method</b>	only upwards
<b>Type of luminaires</b>	OZ 400 - lamp's diffuser collar diameter $\varnothing 180$ mm



## TABLE OF VARIANTS

Code	Symbol	Power	Unit volume	Effective projected area	Colour	Light source type	Lamp diffuser neck	Type of diffuser	Net weight
211415	OZ 400	23 W	0.01 m <sup>3</sup>	0.13 m <sup>2</sup>	• black	LED E-27	180 mm	Sphere 400	0.35 kg

: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC(Official Journal of the UE L 285/10 31.10.2009)

: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019, PN-EN 61000-3-3: 2014

Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

## TECHNICAL DRAWING

