



TECHNICAL DATA

Assembly	on extension arms with ø 60 x 100 mm ending
Application	urban roads, residential roads (internal), pedestrians, parkings
Colour	inox / black
Ingress protection	IP 66 for the optical part and the driver
Optical system	PMMA optics, interchangeable LED module
Material	cap – formed aluminium sheet diffuser - tempered glass luminaire body - aluminum alloy, anodized
Unit volume	0,068 m³
Operating temperature range	from -40°C to +40°C
Expected useful lifetime	L90B10 - 100 000 h
CRI	>70
Inrush current	18 A / 280 µs (36 W) 32 A / 355 µs (48 W) 98 A / 120 µs (60 W)
Input voltage frequency	50 - 60Hz
Power factor	≥0,95
Number of LED	16
Control system	Luminaire has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1- 10V).



TABLE OF VARIANTS

Code	Symbol	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux¹	Luminaire luminous flux¹	Luminous efficacy¹	Net weight
2211032/1...²	COSMO LED 36	36 W	39 W	375 mA	2700 K	6200 lm	5150 lm	132 lm/W	8,3 kg
2211032/3...²	COSMO LED 36	36 W	39 W	375 mA	3500 K	6500 lm	5400 lm	138 lm/W	8,3 kg
2211032/4...²	COSMO LED 36	36 W	39 W	375 mA	4000 K	6650 lm	5500 lm	141 lm/W	8,3 kg
2211032/6...²	COSMO LED 36	36 W	39 W	375 mA	5000 K	6550 lm	5450 lm	140 lm/W	8,3 kg
2211033/1...²	COSMO LED 48	48 W	54 W	500 mA	2700 K	7950 lm	6600 lm	122 lm/W	8,3 kg
2211033/3...²	COSMO LED 48	48 W	54 W	500 mA	3500 K	8300 lm	6900 lm	128 lm/W	8,3 kg
2211033/4...²	COSMO LED 48	48 W	54 W	500 mA	4000 K	8550 lm	7100 lm	131 lm/W	8,3 kg
2211033/6...²	COSMO LED 48	48 W	54 W	500 mA	5000 K	8450 lm	7000 lm	130 lm/W	8,3 kg
2211034/1...²	COSMO LED 60	60 W	67 W	625 mA	2700 K	9650 lm	8000 lm	119 lm/W	8,3 kg
2211034/3...²	COSMO LED 60	60 W	67 W	625 mA	3500 K	10100 lm	8400 lm	125 lm/W	8,3 kg
2211034/4...²	COSMO LED 60	60 W	67 W	625 mA	4000 K	10350 lm	8600 lm	128 lm/W	8,3 kg
2211034/6/...²	COSMO LED 60	60 W	67 W	625 mA	5000 K	10250 lm	8500 lm	127 lm/W	8,3 kg

1) tolerance +/- 5% due to LEDs accuracy

2) symbol of chosen optical system eg. 2211034/6/T3 is COSMO LED 72 5000 K with T3 optical system

DIRECTIVES AND STANDARDS

DIRECTIVES: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC(Official Journal of the UE L 285/10 31.10.2009)

STANDARDS: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019 , PN-EN 61000-3-3: 2014


Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

REMOVING ELECTROSTATIC CHARGE FROM LED LUMINAIRE BODY


In order to efficient discharge the electrostatic charge from the housing of LED fitting installed on the pole from dielectric material (non-conductive) one of the following solutions is required:


- functional grounding
- LED luminaire with an additional protection device

TECHNICAL DRAWING



PHOTOMETRIC CURVES





POWER SYSTEM FUNCTIONS

Luminaire in standard has following functions of intelligent power supply:

- Connection to outside control system by DALI interface (operation of analog signal 1-10V as an option),
- Possibility of programming multistage dimming of luminaire, up to 5 intervals in the range of from 10 to 100% of nominal power,
- LED module equipped with thermal protection implemented via an NTC thermistor,
- Regulation of power / luminous flux – the option of setting another value than the catalogue in the range of 30-100% of nominal one,

ACCETABLE QUANTITY OF LUMINAIRES ON ONE CIRCUIT

Overcurrent switches MCB type B or C

Luminaire	Typ	2 A	4 A	6 A	10 A	16 A	20 A	25 A
COSMO LED 36 W	B	4	7	12	18	30	37	46
	C	4	12	18	31	51	62	78
COSMO LED 48 W, 60 W	B	1	2	4	6	10	12	15
	C	1	4	6	10	17	20	26

Fuse – type gG and GL

Luminaire	2 A	4 A	6 A	10 A	16 A	20 A	25 A
COSMO LED 36 W	1	10	20	26	52	71	101
COSMO LED 48 W	0	5	10	13	26	35	50
COSMO LED 60 W	0	2	5	7	14	20	28