



TECHNICAL DATA

Application	urban roads, residential roads (internal), surrounding office buildings, parks, pedestrians
Colour	inox / grey
Ingress protection	IP 66 for the optical part and the driver
Optical system	PMMA optics, interchangeable LED module
Material	anodised aluminium alloy
Expected useful lifetime	L90B10 - 100 000 h
CRI	>70
Input voltage frequency	50/60Hz
Power factor	≥0.95
Number of LED	12 - (24 W, 36 W), 24 - (48 W, 72 W)
Control system	LED lighting set has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1-10V).




TABLE OF VARIANTS

Code	Symbol	Height of the column [H]	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux ¹	Luminaire luminous flux ¹	Luminous efficacy ¹	Unit volume	Concrete footing / reinforcement basket type	Inrush current	Net weight
216230/1/... ²	CUT-3 LED 24	3 m	24 W	28 W	700 mA	2700 K	4050 lm	3550 lm	127 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216230/3/... ²	CUT-3 LED 24	3 m	24 W	28 W	700 mA	3500 K	4350 lm	3800 lm	136 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216230/4/... ²	CUT-3 LED 24	3 m	24 W	28 W	700 mA	4000 K	4550 lm	4000 lm	143 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216230/6/... ²	CUT-3 LED 24	3 m	24 W	28 W	700 mA	5000 K	4550 lm	4000 lm	143 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216232/1/... ²	CUT-3 LED 36	3 m	36 W	40 W	1000 mA	2700 K	5450 lm	4800 lm	120 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216232/3/... ²	CUT-3 LED 36	3 m	36 W	40 W	1000 mA	3500 K	5800 lm	5100 lm	128 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216232/4/... ²	CUT-3 LED 36	3 m	36 W	40 W	1000 mA	4000 K	6150 lm	5400 lm	135 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216232/6/... ²	CUT-3 LED 36	3 m	36 W	40 W	1000 mA	5000 K	6150 lm	5400 lm	135 lm/W	0.5 m ³	B-50 / Z-50	18A / 280µs	31 kg
216330/1/... ²	CUT-4 LED 24	4 m	24 W	28 W	700 mA	2700 K	4050 lm	3550 lm	127 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216330/3/... ²	CUT-4 LED 24	4 m	24 W	28 W	700 mA	3500 K	4350 lm	3800 lm	136 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216330/4/... ²	CUT-4 LED 24	4 m	24 W	28 W	700 mA	4000 K	4550 lm	4000 lm	143 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216330/6/... ²	CUT-4 LED 24	4 m	24 W	28 W	700 mA	5000 K	4550 lm	4000 lm	143 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216332/1/... ²	CUT-4 LED 36	4 m	36 W	40 W	1000 mA	2700 K	5450 lm	4800 lm	120 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216332/3/... ²	CUT-4 LED 36	4 m	36 W	40 W	1000 mA	3500 K	5800 lm	5100 lm	128 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216332/4/... ²	CUT-4 LED 36	4 m	36 W	40 W	1000 mA	4000 K	6150 lm	5400 lm	135 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216332/6/... ²	CUT-4 LED 36	4 m	36 W	40 W	1000 mA	5000 K	6150 lm	5400 lm	135 lm/W	0.7 m ³	B-50 / Z-50	18A / 280µs	37.5 kg
216333/1/... ²	CUT-4 LED 48	4 m	48 W	55 W	700 mA	2700 K	8150 lm	7150 lm	130 lm/W	0.7 m ³	B-50 / Z-50	46A / 250µs	37.5 kg
216333/3/... ²	CUT-4 LED 48	4 m	48 W	55 W	700 mA	3500 K	8650 lm	7600 lm	138 lm/W	0.7 m ³	B-50 / Z-50	46A / 250µs	37.5 kg
216333/4/... ²	CUT-4 LED 48	4 m	48 W	55 W	700 mA	4000 K	9150 lm	8050 lm	146 lm/W	0.7 m ³	B-50 / Z-50	46A / 250µs	37.5 kg
216333/6/... ²	CUT-4 LED 48	4 m	48 W	55 W	700 mA	5000 K	9150 lm	8042 lm	146 lm/W	0.7 m ³	B-50 / Z-50	46A / 250µs	37.5 kg

216030/1/... ²	CUT-5 LED 24	5 m	24 W	28 W	700 mA	2700 K	4050 lm	3550 lm	127 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216030/3/... ²	CUT-5 LED 24	5 m	24 W	28 W	700 mA	3500 K	4350 lm	3800 lm	136 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216030/4/... ²	CUT-5 LED 24	5 m	24 W	28 W	700 mA	4000 K	4550 lm	4000 lm	143 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216030/6/... ²	CUT-5 LED 24	5 m	24 W	28 W	700 mA	5000 K	4550 lm	4000 lm	143 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216032/1/... ²	CUT-5 LED 36	5 m	36 W	40 W	1000 mA	2700 K	5450 lm	4800 lm	120 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216032/3/... ²	CUT-5 LED 36	5 m	36 W	40 W	1000 mA	3500 K	5800 lm	5100 lm	128 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216032/4/... ²	CUT-5 LED 36	5 m	36 W	40 W	1000 mA	4000 K	6150 lm	5400 lm	135 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216032/6/... ²	CUT-5 LED 36	5 m	36 W	40 W	1000 mA	5000 K	6150 lm	5400 lm	135 lm/W	1 m ³	B-50 / Z-50	18A / 280µs	42.5 kg
216033/1/... ²	CUT-5 LED 48	5 m	48 W	55 W	700 mA	2700 K	8150 lm	7150 lm	130 lm/W	1 m ³	B-50 / Z-50	46A / 250µs	42.5 kg
216033/3/... ²	CUT-5 LED 48	5 m	48 W	55 W	700 mA	3500 K	8650 lm	7600 lm	138 lm/W	1 m ³	B-50 / Z-50	46A / 250µs	42.5 kg
216033/4/... ²	CUT-5 LED 48	5 m	48 W	55 W	700 mA	4000 K	9150 lm	8050 lm	146 lm/W	1 m ³	B-50 / Z-50	46A / 250µs	42.5 kg
216033/6/... ²	CUT-5 LED 48	5 m	48 W	55 W	700 mA	5000 K	9150 lm	8042 lm	146 lm/W	1 m ³	B-50 / Z-50	46A / 250µs	42.5 kg
216633/1/... ²	CUT-6 LED 48	6 m	48 W	55 W	700 mA	2700 K	8150 lm	7150 lm	130 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216633/3/... ²	CUT-6 LED 48	6 m	48 W	55 W	700 mA	3500 K	8650 lm	7600 lm	138 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216633/4/... ²	CUT-6 LED 48	6 m	48 W	55 W	700 mA	4000 K	9150 lm	8050 lm	146 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216633/6/... ²	CUT-6 LED 48	6 m	48 W	55 W	700 mA	5000 K	9150 lm	8042 lm	146 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216635/1/... ²	CUT-6 LED 72	6 m	72 W	79 W	1000 mA	2700 K	10900 lm	9600 lm	122 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216635/3/... ²	CUT-6 LED 72	6 m	72 W	79 W	1000 mA	3500 K	11600 lm	10200 lm	129 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216635/4/... ²	CUT-6 LED 72	6 m	72 W	79 W	1000 mA	4000 K	12300 lm	10800 lm	137 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216635/6/... ²	CUT-6 LED 72	6 m	72 W	79 W	1000 mA	5000 K	12300 lm	10800 lm	137 lm/W	1.2 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	62.5 kg
216733/1/... ²	CUT-7 LED 48	7 m	48 W	55 W	700 mA	2700 K	8150 lm	7150 lm	130 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216733/3/... ²	CUT-7 LED 48	7 m	48 W	55 W	700 mA	3500 K	8650 lm	7600 lm	138 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216733/4/... ²	CUT-7 LED 48	7 m	48 W	55 W	700 mA	4000 K	9150 lm	8050 lm	146 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216733/6/... ²	CUT-7 LED 48	7 m	48 W	55 W	700 mA	5000 K	9150 lm	8042 lm	146 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216735/1/... ²	CUT-7 LED 72	7 m	72 W	79 W	1000 mA	2700 K	10900 lm	9600 lm	122 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216735/3/... ²	CUT-7 LED 72	7 m	72 W	79 W	1000 mA	3500 K	11600 lm	10200 lm	129 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216735/4/... ²	CUT-7 LED 72	7 m	72 W	79 W	1000 mA	4000 K	12300 lm	10800 lm	137 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216735/6/... ²	CUT-7 LED 72	7 m	72 W	79 W	1000 mA	5000 K	12300 lm	10800 lm	137 lm/W	1.4 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	69.5 kg
216433/1/... ²	CUT-8 LED 48	8 m	48 W	55 W	700 mA	2700 K	8150 lm	7150 lm	130 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg
216433/3/... ²	CUT-8 LED 48	8 m	48 W	55 W	700 mA	3500 K	8650 lm	7600 lm	138 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg
216433/4/... ²	CUT-8 LED 48	8 m	48 W	55 W	700 mA	4000 K	9150 lm	8050 lm	146 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg
216433/6/... ²	CUT-8 LED 48	8 m	48 W	55 W	700 mA	5000 K	9150 lm	8042 lm	146 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg
216435/1/... ²	CUT-8 LED 72	8 m	72 W	79 W	1000 mA	2700 K	10900 lm	9600 lm	122 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg
216435/3/... ²	CUT-8 LED 72	8 m	72 W	79 W	1000 mA	3500 K	11600 lm	10200 lm	129 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg
216435/4/... ²	CUT-8 LED 72	8 m	72 W	79 W	1000 mA	4000 K	12300 lm	10800 lm	137 lm/W	1.6 m ³	B-71, B-70 / Z-71, Z-70	46A / 250µs	76 kg

216435/6/...² CUT-8 LED 72 8 m 72 W 79 W 1000 mA 5000 K 12300 lm 10800 lm 137 lm/W 1.6 m³ B-/1, B-/U / L-/1, 46A / Z-70 250µs 76 kg

1) tolerance +/- 5% due to LEDs accuracy

2) symbol of chosen optical system eg. 216230/6/T2 is CUT-3 LED 24 5000K with T2 optical system


DIRECTIVES AND STANDARDS

DIRECTIVES: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE RoHS (Official Journal of the UE L 174/88 01.07.2011), 2009/125/EC (Official Journal of the UE L 285/10 31.10.2009)


STANDARDS: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471: 2010, PN-EN 55015: 2019, PN-EN 61547: 2009, PN-EN 61000-3-2: 2019, PN-EN 61000-3-3: 2014


Lighting parameters presented based on laboratory tests according to IESNA LM-79-19

TECHNICAL DRAWING



PHOTOMETRIC CURVES





POWER SYSTEM FUNCTIONS

Luminaire in standard has following functions of intelligent power supply:

- Connection to outside control system by DALI interface (operation of analog signal 1-10V as an option),
- Possibility of programming multistage dimming of luminaire, up to 5 intervals in the range of from 10 to 100% of nominal power,
- LED module equipped with thermal protection implemented via an NTC thermistor,
- Regulation of power / luminous flux – the option of setting another value than the catalogue in the range of 30-100% of nominal one,

ACCEPTABLE QUANTITY OF LUMINAIRES ON ONE CIRCUIT

Overcurrent switches MCB type B or C

Lighting sets	Typ	2A	4A	6A	10A	16A	20A	25A
CUT LED 24, 36W	B	3	6	10	16	26	32	40
	C	3	10	16	27	44	54	67
CUT LED 48, 72W	B	1	2	4	6	11	13	17
	C	1	4	6	11	18	22	28

Fuse – type gG and GL

Lighting sets	2A	4A	6A	10A	16A	20A	25A
CUT LED 24, 36W	1	10	19	25	50	68	97
CUT LED 48, 72W	0	4	8	11	21	29	42

ACCEPTABLE HEIGHT

CUT LED-3/4/5 Acceptable height of the LED lighting set

Field category	I zone Vref. = 22 m/s	I & III zone, up to 450m a.s.l. Vref. = 24 m/s	II zone Vref. = 26 m/s	III zone up to 755m a.s.l. Vref. = 28 m/s
I	6	5,5	5	4,5
II	6	5,5	5,5	5
III	6	6	5,5	5,5
IV	6	6	6	6

CUT LED-6/7/8 Acceptable height of the LED lighting set

Field category	I zone Vref. = 22 m/s	I & III zone, up to 450m a.s.l. Vref. = 24 m/s	II zone Vref. = 26 m/s	III zone up to 755m a.s.l. Vref. = 28 m/s
I	7,5	7	6,5	6
II	8	7,5	7	6,5
III	8	8	7,5	7
IV	8	8	8	7,5