



260mm at the base plate



Anodising	10 colours
Packing	sleeve material
Diameter at the base plate	260mm
Finish	brushed anodised aluminium - anode coating thickness is 20µm as standard (coating thickness of 25µm is also possible), option of elastomer protection up to a height of 350 mm, in a colour similar to the anode colour (other heights or colours of elastomer available according to the RAL palette at the customer's request) - the thickness of the protective coating ranges from 0.8 mm to 1.2 mm
Purpose	designed for hanging traffic lights at road intersections, pedestrian crossings etc.



Code	Symbol	Height of the column [H]	Wall thickness	Unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners	Net weight
42853/C...	SAL SYG 260-6,5-9	6.5 m	5.5 mm	2.05 m³	Z-80	311208	4012	157.6 kg

SAL SYG 260-6,5-9	Acceptable windage of trac signal lights and signs [m2] for Cx=1,2		
code 42853	Vref. = 22 m/s	Vref. = 22 m/s	Vref. = 24 m/s
Acceptable mass of single trac signal light	I zone, IV Field category	I zone, III Field category	I i III zone, III Field category up to 450m n.p.m.
25 [kg]	1)1,05 m ²	1)0,90m ²	1)0,78m ²

2) In order to determine the foundation dimensions, please send the catalog cards of the equipment that will be installed on the column and its arrangement. For the values presented in the chart and the arrangement of signaling devices as shown in the diagram below, it is recommended to make a cast foundation with dimensions $L \times B \times H = 0,6 \times 0,6 \times 1,6 \text{ m}$

C-0 Natural

C-32 Champagne

C-33 Olive

C-34 Brown

C-35 Black

C-45 Inox

C-63 Grey

C-65 Graphite

C-75 Green

C-78 Anthracite